





Fitted with	LED - Energy efficiency category A+ ø 18 cm
Illuminance field 100 cm	130 000 lx
Illuminance 100 cm	> 96
Colour rendering index (Ra)	Electronic converter
Work equipment	100-240 V; 50/60 Hz
Voltage	Direct power supply
Mains lead	Polyamid (PA)
Luminaire body	20 kg
Weight (net)	40 W
Power consumption	Keypad at cardanic
Usage	Spring
Balance of articulation joints	I
Class of protection	Sterilizable handle, handle cover
Accessory	EN 60601-1, EN 60601-2-41
Norms	Stepless dimmable, focusable, colour changeable, sterilizable handle
Special features	Rolling stand
Fastening	IP 20
System of protection	IP 43 (horizontal position)
Medical device class	I according to MDR

	lighting field / 1,0 m changeable value 14 / 21 / 26 cm	Colour temperature changeable value 3700K / 4300K / 4700K	Dimmable	Order No.
TRIANGO Fokus 130-3 F SCHUKO	X	X	X	D16.292.000
TRIANGO Fokus 130-3 F US-HG	X	X	X	D16.294.000
TRIANGO Fokus 130-3 F CH	X	X	X	D16.295.000
TRIANGO Fokus 130-3 F UK	X	X	X	D16.293.000
TRIANGO Fokus 130-3 F AUS	X	X	X	D16.296.000

Light distribution



Technical drawing

